




## **WARN XT40 The Most Extreme** Side X Side Winch on the Market

If you've got a Side X Side and are looking to outfit it with the most extreme Side X Side winch on the market, look no further than the XT40. It's got 50' of light-weight, easyto-handle synthetic rope; a wireless control system with a 50' range, plus a mini-rocker control switch; and a sealed drivetrain to keep the elements out and the winch working properly. Other features include an all-metal 3-stage planetary geartrain for smooth, reliable operation; a patented disc brake for outstanding control: a short-throw clutch; and an efficient motor for longer pulls with less battery drain.

#### PN 77500





wireless control and handle-bar mounted mini-rocker control switch

Winch Model: XT40 Part Number: 77500 Rated Line Pull: 4.000 lbs. (1814 kgs) single-line Motor: 12V Permanent Magnent Sealing: Full Geartrain: All-metal Rope Material: Synthetic Rope Length & Diameter:

50' x 7/32" (15m x 5.5mm)

SPECIFICATIONS:

**Primary Control:** Handle-bar mini-rocker Remote Control: Wireless Remote Best for Plow Lifting: Yes Disc Brake: Yes Warranty: Limited Lifetime Clutch Control: Ergonomic dial Wiring Diameter: 6-Gauge



## **WARN RT40 A Winching** Workhorse for Side X Sides

Riders looking for on-the-job performance and outstanding durability will want the RT40 for their Side X Side. The winch showcases 4,000 lbs. of pulling muscle and 55' of durable wire rope-the longest in the WARN Powersports lineup. This winch has tons of standard features including a patented disc brake for great control; a fully sealed drivetrain; a reliable and smooth all-metal 3-stage planetary geartrain; short-throw clutch; a corded remote and mini-rocker control switch for winch operation; and an efficient electrical system for long pulls and less battery drain.

#### PN 77000





Kit includes wire rope, handheld corded remote control, and handle-har mounted mini-rocker control switch

## SPECIFICATIONS:


Winch Model: RT40 Part Number: 77000 Rated Line Pull: 4.000 lbs. (1814 kgs) single-line Motor: 12V Permanent Magnent Sealing: Full Geartrain: All-metal Rope Material: Wire

Rope Length & Diameter: 55' x 7/32" (17m x 5.5mm)

**Primary Control:** Handle-har mini-rocker Remote Control: Corded Remote Best for Plow Lifting: No. Disc Brake: Yes Warranty: Limited Lifetime Clutch Control: Ergonomic dial Wiring Diameter: 6-Gauge

#### RT and XT winch performance specs (first laver of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0	25 (7.6)	31	1/4000 (1814)
1000 (455)	16 (4.9)	106	2/3440 (1560)
2000 (907)	11 (3.3)	175	3/2958 (1342)
3000 (1360)	7 (2.1)	245	4/2544 (1154)
4000 (1814)	4 (1.2)	308	



Winch dimensions: 14.4" L. x 4.5" D. x 4.7" H. (36.6Cm L. x 12Cm D. x 12Cm H.)

Mounting bolt pattern: 3.0" x 6.59" (76mm x 167mm)

WINCHES

ROAD PRODUCTS POWERSPORTS



## **WARN XT30 An Extreme Terrain** Winch for Large-Bore Utility ATVs

Riders looking for the most extreme winch on the ATV market will want the XT30. It has a 3,000 lb. line capacity to pull the biggest ATVs; a wireless control system with a 50' range for increased winching options; a short-throw clutch, and 50' of lightweight and easy-to-handle synthetic rope—great for vehicle recovery and plow lifting. Full winch sealing helps keep the elements out, and the all-metal 3-stage planetary geartrain will run smoothly for years. The patented disc brake provides enhanced braking performance, and the efficient electrical system minimizes battery drain.

#### PN 76500





Kit includes synthetic rone, handheld wireless control and handle-bar mounted nini-rocker control switch

## SPECIFICATIONS:

Winch Model: XT30 Part Number: 76500

Rated Line Pull-3.000 lbs. (1361 kgs) single-line

Motor: 12V Permanent Magnent

Sealing: Full

Geartrain: All-metal Rope Material: Synthetic Rope Length & Diameter: 50' x 3/16" (15m x 5mm)

**Primary Control:** Handlebar mini-rocker

Remote Control: Wireless Remote Best for Plow Lifting: Yes

Disc Brake: Yes Warranty: Limited Lifetime

Clutch Control: Ergonomic dial Wiring Diameter: 6-Gauge

## WARN RT30 A Powerhouse Winch for Big Utility ATVs

With 3,000 lbs, of pulling power and 50' of durable wire rope, the RT30 is a powerhouse ATV winch. Get-it-done features include an all-metal 3-stage planetary geartrain; full sealing to help keep the elements out; and a patented disc brake for optimum braking performance. With a corded remote, a handlebar-mounted mini-rocker switch and a short-throw clutch, the RT30 provides a great combination of power and control

PN 76000, PN 81500 (CE. International sales only)





Kit includes wire rope, handheld corded remote control, and handle-bar mounted mini-rocker control switch

#### SPECIFICATIONS:

Winch Model: RT30 Part Number: 76000, 81500 (CE, International sales only)

Rated Line Pull: 3,000 lbs. (1361 kgs) single-line

Motor: 12V Permanent Magnent Sealing: Full Geartrain: All-metal

Rope Material: Wire Rope Length & Diameter: 50' x 3/16" (15m x 5mm)

**Primary Control:** Handlebar mini-rocker


Remote Control: Corded Remote Best for Plow Lifting: No

Disc Brake: Yes Warranty: Limited Lifetime

Clutch Control: Ergonomic dial Wiring Diameter: 6-Gauge

#### RT and XT winch performance specs (first laver of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0	18 (5.5)	15	1/3000 (1360)
1000 (455)	13 (4.0)	67	2/2580 (1170)
2000 (907)	8 (2.4)	125	3/2220 (1007)
3000 (1360)	4 (1.2)	198	4/1910 (866)



Winch dimensions 13.1" L. x 4.53" D. x 4.69" H. (33.3Cm L, x 11.5Cm D, x 11.9Cm H,)

Mounting bolt pattern: 3.0" x 4.87" (76mm x 124mm)





## **WARN XT25 For Utility ATVs** 350cc and Up

Take the trail less traveled with the XT25. With its 2,500 lb. line capacity and 50' of synthetic rope, you'll be able to recover your vehicle (or your buddy's vehicle) with ease; it's great for plow lifting, too, The XT25 showcases an all-metal 3-stage planetary geartrain for smooth, reliable operation; a handlebarmounted mini-rocker switch for convenient control: a short-throw clutch; and fast line speed. A patented disc brake ensures positive control while winching; full sealing keeps the elements out; and the efficient electrical system minimizes battery drain and keeps your winch working time after time.

PN 75500, PN 81000 (CE, International sales only)



SPECIFICATIONS:

Winch Model: RT25

Part Number: 75500.

Geartrain: All-metal

Rope Material: Wire

Rope Length & Diameter: 50' x 3/16" (15m x 5mm)

Rated Line Pull-

Sealing: Full





Remote Control: None Best for Plow Lifting: Yes 81000 (CE, International sales only) Disc Brake: Yes 2,500 lbs. (1361 kgs) single-line Warranty: Limited Lifetime Motor: 12V Permanent Magnent Clutch Control: Ergonomic dial Wiring Diameter: 8-Gauge

Primary Control: SPECIFICATIONS: Handlehar mini-rocker

Winch Model: XT25 Part Number: 75000. 80500 (CE. International sales only) Rated Line Pull-2,500 lbs. (1234 kgs) single-line Motor: 12V Permanent Magnent Sealing: Full

Geartrain: All-metal Rope Material: Synthetic Rope Length & Diameter:

## WARN RT25 The Best Selling ATV Winch for Work or Play

The RT25 is a versatile, durable winch with a just-right 2,500 lb. pulling capacity and 50' of durable wire rope—making it perfect fit for Utility ATVs 350cc and up. This industry-standard winch has an all-metal 3-stage planetary geartrain; full sealing to keep the elements out; a patented disc brake for excellent control; a short-throw clutch; and an efficient electrical system for less battery drain. A handlebar-mounted mini-rocker switch provides simple, effective control.

PN 75000, PN 80500 (CE, International sales only)






50' x 3/16" (15m x 5mm)

Primary Control: Remote Control: None Best for Plow Lifting: No Disc Brake: Yes Warranty: Limited Lifetime Clutch Control: Ergonomic dial Wiring Diameter: 8-Gauge

RT and XT winch performance specs (first layer of drum)

Line Pull Lbs. (Kgs.) O	Line Speed Ft./min. (M/min.) 18 (5.5)	Motor Current 15	Pull by layer: layer/Lbs (Kgs.) 1/2500 (1134)
500 (227)	16 (4.9)	39	2/2150 (975)
1500 (680)	10 (3.0)	96	3/1845 (836)
2500 (1134)	5 (1.5)	157	4/1586 (719)



WWW.WARN.COM



ROAD PRODUCTS POWERSPORTS WINCHES

## **WARN XT15** For Sport and Utility ATVs Under 300cc

With a 1,500 lb. pulling capacity and 40' of lightweight, easy-to-handle synthetic rope, the XT15 was tailor-made for sport guads and small ATVs. Features include a patented disc brake for excellent control; a 3-stage planetary geartrain for smooth, reliable operation; a sealed motor to keep the elements out; and a handlebar-mounted mini-rocker control for easy operation. This winch is also great for plow lifting. PN 78500



## WARN RT15 A Pulling Tool for **Smaller Quads With Big Ideas**

The RT15 is the perfect all-around winch for sport quads and small ATVs under 300cc. Its 1,500 lb, capacity and 50' of wire rope turns compact ATVs into workhorses. Features include a 3-stage planetary geartrain; a patented disc brake for great control; a sealed motor to keep the elements out; and a handlebar-mounted mini-rocker switch for power in/ power out. An efficient electrical system for less battery drain and a hawse fairlead round out the RT15's features. PN 78000





mounted mini-rocker control switch

SPECIFICATIONS: Winch Model: XT15 Part Number: 78500

Rated Line Pull: 1,500 lbs. (680 kgs) single-line

Sealing: Motor

Geartrain: 3 stage planetary Rope Material: Synthetic Rope Length & Diameter:

40' x 5/32" (12m x 4mm) **Primary Control:** 



Handlehar mini-rocker

Remote Control: None Best for Plow Lifting: Yes Disc Brake: Yes 1,500 lbs. (680 kgs) single-line

Warranty: Limited Lifetime Sealing: Motor Clutch Control: Cam Activated Wiring Diameter: 10-Gauge

SPECIFICATIONS:

Winch Model: RT15 Part Number: 78000 **Rated Line Pull:** 

Geartrain: 3 stage planetary Rope Material: Wire

Rope Length & Diameter: 50' x 5/32" (15m x 4mm) **Primary Control:** 

Kit includes wire rope and handle-bar mounted mini-rocker control switch

Handlebar mini-rocker

Remote Control: None Best for Plow Lifting: No Disc Brake: Yes

Warranty: Limited Lifetime


Clutch Control: Cam Activated

Wiring Diameter: 10-Gauge

#### RT and XT winch performance specs (first layer of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0	15 (4.6)	6	1/1500 (680)
500 (227)	11 (3.3)	27	2/1320 (599)
1000 (455)	7 (2.1)	44	3/1162 (527)
1500 (680)	5 (2.1)	65	4/1020 (463)









## WARN SnoWinch™

## **Portable Winch System**

With 1,500 lbs, of pulling capacity, the SnoWinch will get your battery-equipped vehicle back on the trail in a hurry. Amenities include an patented disc brake and rigging straps that makes setup easy. SnoWinch comes with 40' of lightweight, easy-to-handle synthetic rope; 9' and 25' recovery straps; and a handheld remote with a 121/2' lead. PN 70170



Synthetic rope comes standard






### SPECIFICATIONS:

Winch Model: SnoWinch Part Number: 70170 Rated Line Pull: 1,500 lbs. (680 kgs) single-line Geartrain: 3-stage planetary Rope Material: Synthetic Rope Length & Diameter: 40' x 5/32" (12m x 4mm)

Remote Control: Yes Best for Plow Lifting: No Disc Brake: Yes Warranty: Limited 1 Year Clutch Control: Cam activated Wiring Diameter: 10-Gauge

#### 12V DC performance specs (first layer of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0	15 (4.6)	6 amps	1/1500 (680)
500 (227)	11 (3.3)	27 amps	2/1320 (599)
1000 (455)	7 (2.1)	44 amps	3/1162 (527)
1500 (680)	5 (1.5)	65 amps	4/1020 (463)



WWW.WARN.COM



68



#### **Dual Battery Control Kit**

- · Lets you use two batteries, but saves the main battery for essential functions, such as starting the vehicle.
- · Engineered specifically to give maximum power during winch power-in operation.
- · For use with 12-volt accessories such as winches, lights, stereos and more
- . Minimizes charging system overload; if both batteries need charging, the main battery is charged first.
- · Optional manual override forces a parallel connection when you need extra power for accessories or jumpstarting another vehicle.
- . Designed for use with 12-volt DC magneto or alternator charging systems.
- · Easy to install; includes all necessary hardware. (Second battery not included)

PN 77977



# for ATVs and Side X Sides

The WARN Wireless Control System will work with WARN 1.5ci. 2.5ci. 3.0ci winches: and all RT/XT series winches.\* The system is quick and easy to install thanks to a wiring harness with integrated antenna and included mounting hardware. The system lets you operate your winch from anywhere within a 50' radius, giving you more recovery options. The system's two-button transmitter allows for easy operation, even while wearing gloves. A two-color LED provides instant feedback during the winching process, and the system shuts off automatically after three minutes (or it can be turned off manually) to conserve battery life. A convenient handlebar or dash-mounted holster securely holds the transmitter when not in use.

PN 74500 Wireless Winch Control System

PN 74520 Transmitter only

\* May not work with WARN co-branded winches. Call WARN Customer Service for details.

#### F) Tree Trunk Protector A) Winching Accessory Kit

The WARN Accessory Kit is essential gear for getting the 6,400 lbs.) PN 28882

(25.4mm x 2.4m) tree trunk protectors. Each kit comes in a black heavyweight nylon soft case. PN 69222 Kit with black nylon soft case PN 63351 Black bag only

WINCHING ACCESSORIES

Double your pulling power, change your pulling

direction, and keep your winch in proper working order.

most out of your WARN Powersports winch. Accessory

Kits include two shackles, snatch block, and two 1"x 8'

#### B) Guide To Winching

The Basic Guide to Winching Techniques is a "must read" booklet that helps you learn the important facts concerning the proper use of your winch. Free download available at www.warn.com. PN 64660

#### c) Snatch Block

Assists in double-lined and angled pulls. Rated to 8,000 lbs. (3,628.74 kg) capacity and under.

#### PN 28881

#### D) Shackle

Shackle for rigging attachments, Rated to 8,000 lbs. (3,628.74 kg) capacity and under. PN 28884

### E) Mini-Rocker Control Switch With Integrated Socket

This kit allows you to plug in a corded remote directly into the mini-rocker switch-no need to drill and install the socket like on existing systems. This allows you to conveniently winch while on or off the vehicle. Kit includes mini-rocker switch with socket, corded remote, and all necessary hardware.

#### PN 80588

\* Not compatible with PN 64849

#### K) Replacement Contactor Four-post, weather-resistant contactor

handles high amps.

## PN 76429

For RT/XT40 or 4.0ci winches.

PN 63070 For XT/RT 25, 30 series. 2.5ci or 3.0ci winches (pictured above).

#### PN 69281

For RT/XT 15 series or 1.5ci winches.

PN 70755 For SnoWinch.

#### L) Replacement Mini-**Rocker Control Switch**

Handlebar mounted control. Replacement part for the WARN RT/XT 15, 25, 30 series, 3.0ci, 2.5ci or 1.5ci ATV winches, or the WARN Plow Actuator control. Includes switch and mounting hardware.

#### PN 64851

For RT/XT 25, 30 series, 3.0ci or 2.5ci winches.

#### PN 69206

For RT/XT 15 series or 1.5ci winches.

PN 69660 For Plow Actuator.

PN 77944 For Power-Pivot.

1" x 8' (25mm x 2.4m) load strap, designed to protect a tree trunk from the damage a wire rope might cause. Designed for ATV use only. (Rated to

#### g) Neoprene Winch Cover

Made of durable, tight-fitting neoprene that resists water and cracking.

PN 71072 For RT/XT 15 Series and 1.5ci winches. Note: XT/RT15 winch cover includes 8' (2.4m) winch rigging strap.

PN 71980 For RT/XT 25, 30 series and 2.5ci, 3 Oci winches

PN 71975 For RT40, XT40 and 4.0ci winches.

## н) Winch Upgrade Kit

Converts the WARN A2000 to the 2500 lb. capacity winch. Comes with the contactor, wiring, and minirocker control switch

#### PN 63990

### 1) Remote Control Upgrade Kit

Everything you need to add the versatile hand-held remote control to your RT/XT 25 series or RT/XT 15 series, 2.5ci or 1.5ci winches. Comes with remote control, socket, and wiring.

#### PN 64259

#### J) Replacement Remote Control

PN 64849 Corded remote for WARN ATV and Side X Side winches (remote only).

PN 70756 Corded remote for the WARN SnoWinch (remote only).

PN 74520 Transmitter for Wireless Winch Control System.

PN 80958 For use with Mini-Rocker Control Switch with Integrated Socket

WARN CUSTOMER SERVICE: (800) 543-9276






ROAD PRODUCTS POWERSPORTS

### WINCH MOUNTING KITS FOR ATVS AND SIDE X SIDES



To order the right kit for your ATV or Side X Side: Part numbers are listed on the master application chart in the Powersports catalog. Warn Industries is constantly developing new applications. If you can't find your bike listed there, call WARN Customer Service for the latest applications. In North America call 1-800-543-9276. Customers outside of North America can call 1-503-722-3008. Or check our web site: www.warn.com.



WARN engineers use computer-aided manufacturing and design tools to ensure the WARN mounting kit fits the specific make and model of your vehicle. The mounting kits are then laser cut to the exact dimensions of the vehicle, shaped on a computer controlled press brake, and robotically welded for consistent results.



### **BUMPERS FOR ATVS AND SIDE X SIDES**



For the ultimate in versatility and durability for your Side X Side, WARN offers a variety of bumper styles for popular models. These bumpers have an integrated winch mount, pre-drilled holes for WARN trail lights, and the bumper folds down when needed so you can open the hood. The stout construction and powder-coated wrinkle finish will make these bumpers last for years.







YAMAHA



72

POWERSPORTS

PRODUCTS

### MULTI-MOUNT SYSTEM for ATVs and Side X Sides



The Multi-Mount winch system is designed to mount to front and rear 11/4" or 2" Class I receivers. These mounting receivers are engineered for specific ATV/Side X Side makes/models and tie into the ATV/Side X Side frame for increased strength and reliability.

#### HOW TO ORDER

You'll Need Four Items:

1) Winch

2) Winch Carrier

3) Ouick Connect Wiring Kit



Choose the set of parts that are right for you:

#### ATV RT/XT 25 or 30 Winch Mounted to a 1-1/4" Receiver:

- 1. Choose a RT/XT 25 or 30 winch.
- 2. Winch carrier designed to fit 1-1/4" receiver. PN 70925
- 3. 50 amp Quick Connect wiring kit for both front and back of vehicle. Includes: 20" winch lead, 48" front battery lead and 96" rear battery lead. PN 70918

#### Side X Side RT/XT40 Winch Mounted to a 2" Receiver:

- 1. Choose a RT/XT40 winch.
- 2. Winch carrier designed to fit 2" receiver. PN 70919
- 3. 175 amp Quick Connect wiring kit for both front and back of vehicle. Includes: 20" winch lead, 48" front battery lead, and 120" rear battery

#### Side X Side RT/XT30 Winch Mounted to a 2" Receiver:

- 1. Choose a RT/XT30 winch.
- 2. Winch carrier designed to fit 2" receiver. PN 70917
- 3. 50 amp Quick-Connect wiring kit for both front and back of vehicle. Includes 20" winch lead, 48" front battery lead, and 120" rear battery lead. PN 70928

#### Side X Side RT/XT30 WINCH MOUNTED TO A 11/4" RECEIVER:

- 1. Choose a RT/XT30 winch.
- 2. Winch carrier designed to fit 11/4" receiver. PN 70925
- 3. 50 an Ouick-Connect wiring kit for both front and back of vehicle. Includes 20" winch lead, 48" front battery lead, and 120" rear battery lead. PN 70928

### **MULTI-MOUNT ACCESSORIES** AND REPLACEMENT PARTS

#### Power Leads With Ouick Connect Plug

50 amp-for use with RT/XT 25 and 30 winches

PN 70939 (20" winch lead)

PN 72886 (48" battery lead)

PN 72888 (96" battery lead)

PN 70927 (120" battery lead)

PN 22681 (Ouick Connect plugs only)

175 amp-for use with RT/XT40 winch:

PN 36080 (28" winch lead)

PN 70926 (48" battery lead)

PN 26405 (90" battery lead)

PN 70717 (120" battery lead)

PN 22680 (Quick Connect plugs only)

#### Wiring Kit (For Rt/Xt 25 And 30 Multi-Mount).

Designed for the Multi-Mount owner who wants to wire a second bike. Kit includes front and rear power leads with 50 amp Ouick Connect plugs. remote control plug with wiring harness, electrical contactor and Express Install installation wires PN 64874

#### Steel Receiver Shackle Bracket

Utilizes a 11/4" Class I receiver as a recovery or pulling point.

#### PN 62041

(Includes bracket, hitch pin and shackle), PN 28884 (Shackle only) For 2" receivers

use PN 29312.

For 2" receiver (black rubber). PN 37509



**Dust Caps For Quick Connect Plugs** PN 60917 for 50 amp plugs.

PN 69847 for 175 amp plugs.

WARN BODY ARMOR for ATVs and Side X Sides

WARN Body Armor lets you push the envelope and ride with confidence by giving your ATV or Side X Side the ultimate underbody protection. WARN Body Armor is made from brushed aircraft-grade aluminum for excellent durability and great looks. Features include reinforcing beads for the ultimate in strength, recessed hardware to keep nuts and bolts safe and secure, and holes for drainage and servicing access. WARN Body Armor will take your mind off damaging your vehicle and let you focus on riding.



#### **BODY ARMOR** COMPONENTS

- 1 A-Arm Kit, Front
- 2 A-Arm Kit, Rear
- (3) Side Chassis Kit
- (4) Chassis Kit



TO ORDER THE RIGHT KIT FOR YOUR ATV OR Side X Side: Part numbers are listed on the master application chart on pages 119-132, or call WARN Customer Service for the latest applications. In North America call 1-800-543-9276. Customers outside of North America can call 1-503-722-3008. Or check our web site: www.warn.com.

Warn Industries recommends the RT/XT40 winch as the best choice for Side X Side applications.



