



WARN Corded PullzAll™ Portable Lifting and Pulling Tool

- Lifts or pulls up to 1,000 lbs. (454 Kg)
- Replaces old-fashioned come-a-longs and chainfalls
- AC version perfect for use where power is available

When you're in the shop and have access to a power source, just plug in PullzAll and let it help you tackle those laborintensive chores. Move heavy machinery. Hoist an engine block. Lift a load precisely into place, then nail it, weld it, whatever it. You think up the task, and PullzAll flat out revolutionizes the amount of work one man can do.

PN 885000 (120V) **PN 885003** (230v EU)

PN 885002 (230V UK)

PN 885004 (230v AUS)

SPECIFICATIONS:

Switch: Forward/reverse Trigger: Variable speed

Power: AC 120V / 230V Wattage: 1200w

Load Limiter: Electronic, with LED

Clutch: None

Brake: Dynamic

Wire Rope: 7/32" X 15' (6mm X 4.6m)

Weight: 15 lbs. (6.8 kg)

Dimensions:

20" L. x 12.50" W. x 13.25" H. (.50m L. x .31m W. x .33m H.)

WARN Cordless PullzAll™

DC Powered Lifting and Pulling Tool

- Lifts or pulls up to 1,000 lbs. (454 Kg)
- Cordless 24V version is great for use in the field
- Includes two rechargeable battery packs (with charger)

When work takes you to more remote locations, bring the mechanical muscle of the portable, cordless PullzAll with you. From tough tasks like pulling pipe to stretching wire fence, you'll come to count on PullzAll to get the job done quickly and effortlessly. You could say the color of versatility on the job is PullzAll red. Comes with two batteries.

PN 885005 PN 885006 (International)

SPECIFICATIONS:

Switch: Forward/reverse Clutch: None Trigger: Variable speed Brake: Dynamic Power: 24 volt DC Wire Rope:

Wattage: 7200w Weight: 18 lbs. (8.2 kg) Battery: Rechargeable NiMH

battery pack (with rapid charger) Load indicator:

7/32" X 15' (6mm X 4.6m)

Dimensions:

20" L. x 12.50" W. x 13.25" H. (.50m L. x .31m W. x .33m H.) Electronic, with LED











WARN 4700 DC Heavy Puller for **Trailers and General Load-Moving**

The 4700 DC boasts a ready-for-anything attitude. Bring on the big loads, the big jobs no one wants to tackle. Couple 60' of wire rope with the powerful three-stage planetary gear train and you've got a peerless load-mover. Pulls up to 4,700 lbs, no problem. PN 94700

Dynamic and Mechanical Braking

Wire rope: 1/4" X 60' (18.3 m)

2-6' (1.8 m) X 6 Gauge Cable

Weight: 42 lbs. (19.1 kg)

Warranty: Limited One Year

Replacement Wire Rope:

Fairlead: Hawse

Electrical leads:

SPECIFICATIONS:

Capacity: 4,700 lbs. (2130 kgs) single line

Switch type: Remote With 12' (3.7 m) Lead Motor: Permanent Magnet


HP: 1.9 hp 3.0" Diameter

Power: 12V DC Gear train: 3-Stage Planetary

Clutch Control: Paddle

12V DC performance specs (first layer of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0 (0)	17.9 (5.5)	47 Amps	1/4700 (2130)
1000 (453.6)	12.8 (3.9)	82 Amps	2/3980 (1800)
2000 (907.2)	10.8 (3.3)	150 Amps	3/3450 (1560)
3000 (1360.8)	8.1 (2.5)	212 Amps	4/3041 (1380)
4000 (1814.4)	5.8 (1.8)	277 Amps	5/2720 (1230)
4700 (2132)	4.3 (1.3)	322 Amps	



12" L. x 19.5" W. x 8.0" H. (.30m L. x .49m W. x .20m H.)

WARN 3700 DC Great for Trailers

and Worksites

The redesigned 3700 DC has heavy-duty power, which makes it ideally suited for work sites. It's the perfect pulling tool for loading trailers, too. Rugged by design, the ultra-reliable 3700 DC makes a great addition to any workforce, pulling up to 3,700 lbs.



PN 93700

SPECIFICATIONS: Capacity:

3,700 lbs. (1680 kgs) single line Switch type:

Remote With 12' (3.7 m) Lead **Motor:** Permanent Magnet

HP: 1.9 hp 3.0" Diameter Power: 12V DC

Gear train: 3-Stage Planetary Warranty: Limited One Year Clutch Control: Lever

Brake:

Dynamic and Mechanical Braking Wire rope: 7/32" X 43' (13 m)

Fairlead: Roller **Electrical leads:**


2-6' (1.8 m) X 6 Gauge Cable Weight: 35 lbs. (16.9 kg)

Replacement Wire Rope:

PN 78987

12V DC performance specs (first layer of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0 (0)	20.4 (6.2)	30 Amps	1/3700 (1680)
500 (226.8)	15.8 (4.8)	76 Amps	2/3410 (1550)
1000 (453.6)	14.2 (4.3)	111 Amps	3/3170 (1440)
2000 (907.2)	10.9 (3.3)	180 Amps	4/2950 (1340)
3000 (1360.8)	7.7 (2.4)	249 Amps	
3000 (1360.8)	7.7 (2.4)	249 Amps	
3700 (1680)	5.4 (1.7)	297 Amps	



Winch dimensions: 18.0" L. x 9.0" W. x 4.6" H. (.45m L. x .24m D. x .22m H.)



WARN 1700 DC Light-Duty Trailer and Utility Winch

The WARN 1700 DC may be a small winch, but it's one big value when you consider the reliability and the overall quality. Built to handle lighter loads (to 1,700 lbs.), this winch is overflowing with upgraded features, including a hand-held remote to control power-in/power-out functions and tie rods for added stability. PN 91700

SPECIFICATIONS:

Capacity: 1,700 lbs. (1361 kgs) single line

Switch type: Remote With 12' (3.7 m) Lead

Motor: Permanent Magnet **HP:** 1.6 hp 3.0" Diameter Power: 12V DC

Gear train: Differential Planetary

Clutch Control: Knob

Brake: Dynamic

Wire rope: 3/16" X 35' (10.7 m)


Fairlead: Hawse **Electrical leads:**

2-6' (1.8 m) X 8 Gauge Cable Weight: 18 lbs. (8.2 kg)

Warranty: Limited One Year Replacement Wire Rope:

12V DC performance specs (first layer of drum)

Line Pull Lbs. (Kgs.)	Line Speed Ft./min. (M/min.)	Motor Current
0(0)	7.6(2.3)	7.9 Amps
500(227)	6.4(2.0)	24.8 Amps
1000(454)	5.4(1.7)	44.8 Amps
1500(680)	4.5(1.4)	64.9 Amps
1700(771)	4.0(1.2)	76.3 Amps



Winch dimensions 20" L. x 9.0" W. x 8.0" H. (.35m L. x .22m D. x .21m H.)

WARN 3000 ACI

A Plug-In Pulling Powerhouse

With a 3,000 lbs. pulling capacity, a TEFC Induction AC motor for a long duty cycle and 100' of 5/16" wire rope, the 3000 ACI just what you need when you need a heavy-hauling ACpowered winch. The perfect fixed-mount station winch. PN 93000

SPECIFICATIONS:

Capacity: 3,000 lbs. (1361 kgs) single line

Switch type: Drum switch/

station type Motor: TEFC induction AC motor

HP: 0.7 hp 56C

Power: 115/230 volt **Gear train:** 3-Stage Planetary

Clutch Control: Paddle

Brake: Dynamic and Mechanical

Wire rope: 5/16" X 100' (30.5 m)

Fairlead: None


Electrical leads: None Weight: 76 lbs. (34.5 kg) Warranty: Limited One Year

Replacement Wire Rope:

PN 27110

120V DC performance specs (first layer of drum)

Line Pull	Line Speed	Motor	Pull by layer:
Lbs. (Kgs.)	Ft./min. (M/min.)	Current	layer/Lbs (Kgs.)
0(0)	12.2(3.7)	9.1 Amps	1/3000(1361)
1000(453.6)	8.8(2.7)	11.0 Amps	2/2700(1225)
1500(680.4)	8.8(2.7)	12.7 Amps	3/2460(1116)
2000(907.2)	8.6(2.6)	14.8 Amps	4/2250(1021)
2500(1134)	8.5(2.6)	17.7 Amps	5/2070(939)
3000(1360.8)	8.1(2.5)	20.9 Amps	



11" L. x 29" W. x 13" H. (.28m L. x .74m W. x .33m H.)



Utility Winch Accessories



Car Charger 24v

For cordless PullzAll

PN: 685012



Battery Replacement

For cordless PullzAll

PN: 685013

Utility Winch Rigging Kit

- Snatch block, rated to 7,000 lbs.
- 5/8" D-shackles Load/anchor strap rated to 14,400 lbs.
- Nylon soft carrying case

PN 70792



- Controls your WARN 3700 and 4700 winches from up to 50' away
- Activation sequence guards against accidental power-ups
- Weather-resistant transmitter is easy to use



Remote Control

 Replacement remote control for WARN 3700 and 4700 winches with a 30' lead

PN: 69175

Quick Connect Plugs

 Allows for convenient connect/ disconnect to the battery power source

PN: 65707

PullzAll Rigging Kit

- Carry bag designed to hold PullzAll and rigging items
- 5/8" D-shackles Two load anchor straps

PN: 685014



Portable Anchor Plate

- Mounting platform for WARN Utility winches
- Allows the winch to be portable and anchored to a variety of objects

PN 70770



Roller Fairlead

- Assists in guiding the wire rope onto the winch drum
- Extends wire rope life
- Upgrade for WARN 1700/4700 winches

PN 64952



Hitch Adaptor

- Use to mount WARN Utility winches
- Mounts to 2" Class III receiver Black powder coat finish
- · Hitch pin included

PN 68531